

DONE-E

PHH-系列洁净烘箱 Clean Oven

Class 1000# | Class 10000# |



【洁净烘箱】 CLEAN OVEN

PHH-2、PHH-3、PHH-4、PHH-5

主要规格和技术参数 Specifications

| 型号 Model | | PHH-2 | PHH-3 | PHH-4 | PHH-5 |
|-------------------------------------|--|---|---------------|---------------|-------|
| 洁净度 Clean Class | | Class 1000 # 、 Class 10000 # Federal Standards 209E | | | |
| 电源 Power supply | | AC380V 3 50HZ | | | |
| 功率(KVA) Power (KVA) | | 4.5 | 6 | 8 | 11 |
| 工作环境温度 Operating temperature | | 5 ~ +35 | | | |
| 性能 Performance | 温度范围 Temperature range | +20 ~ +250 | | | |
| | 温度波动度 Temperature fluctuation | ± 0.5 | | | |
| | 温度均匀性 Temperature uniformity | 200 ± 3 | 250 ± 4 | | |
| | 升温时间 Temperature heat-up rate | 40分钟以内 (室温 ~ +250) Within 40 min (Ambient temperature ~ +250) | | | |
| 结构 Construction | 外壳 Exterior Material | 防锈处理冷轧钢板(表面喷塑处理) Cold-nolled rust-proof steel plate (Urethane resin electrostatic coating) | | | |
| | 内胆 Interior material | SUS304 # 日制阳极不锈钢 SUS304 # Stainless steel | | | |
| | 隔热材料 Insulation | 玻璃棉 Glass wool | | | |
| | 加热器 Heater | 覆套式电热器 Sheathed Heater | | | |
| | 进气口 Inlet | (N2 or Press air) 8mm | | | |
| | 出气口 Outlet | 50mm排风门 50mm Exhaust door | | | |
| 温度控制系统 Temperature controller | 调节方式 Control mode | PID控制方式 PID control | | | |
| | 运转方式 Operating mode | 定值运转, 程序运转 Constant operation, Programme operation | | | |
| | 设定范围 Setting range | 0 ~ +250 | | | |
| | 设定方式 Setting mode | 数字式 Digital | | | |
| | 显示方式 Display | LED数字显示 LED display | | | |
| | 传感元件 Sensor | K型热电偶 Thermocouple type K | | | |
| | 安全保护 Safety system | 输入断线检测功能、上限温度过热报警功能、蜂鸣器报警功能、自动温度过热防止功能、自行诊断功能 Input burn-out detection function, Upper temperature limit alarm, Buzzer alarm, Over-heat protection, Self diagnostic function | | | |
| 定时功能 Timer | 0.1 ~ 999.9H | | | | |
| 安全保护装置 Safety devices | 电源用漏电断路器、电机温度保护开关、温度保险丝、独立温度过热防止装置 Leakage breaker for power supply, Air circulator temperature switch, Thermal fuse, Overload and short circuit protection for heater, Over-heat protect | | | | |
| 搁板承重能力(kg) Shelf weight capacity | 30 | | | | |
| 内容积(L) Inside capacity(L) | 180 | 270 | 480 | 980 | |
| 重量约(kg) Weight(kg) | 260 | 320 | 450 | 730 | |
| 内部尺寸(W×H×D)mm Inside dimensions | 600×600×500 | 600×900×500 | 800×1000×600 | 1400×1000×700 | |
| 外部尺寸(W×H×D)mm Outside dimensions | 910×1370×740 | 910×1670×740 | 1160×1770×840 | 1760×1770×940 | |
| 附件 Accessories | 搁板 Shelf | 2块 Blocks | | | |
| | 使用说明书 Instruction manual | 1册 Set | | | |
| 选购品 Option | 可编程温控器、记录器、六点温度显示器、三色指示灯 Programmable Temperature Controller, Recorder, Light Tower | | | | |

*1:在环境温度25 时,空载条件下测得的数据;

*2:外尺寸包括鼓风机罩壳和脚轮高度。

*1:The test condition is at 25 ambient temperature non-loaded.

*2:The outside dimensions including motor cover and wheel.

本资料的技术信息如有改动,恕不另行通知;产品以实物为准,图片仅供参考。

Specifications are subject to change without notice due to design improvements. The picture in the specimen are consult only, if there is fluctuation, according to the real object please.



上海旦顺实业有限公司
SHANG HAI DONE-E INDUSTRY CO., LTD.

上海市奉贤区沪杭公路3217号
No. 3217 HuHang Road Shanghai, China
ZIP Code: 201400
Hot line: 400-823-8860
Tel: +86-021-3769 3997
Fax: +86-021-3783 2075
Email: sale@done-e.com
Web: www.done-e.com